

Nucleo-C562RE - Module Datasheet

Module Pins

Module	GPIO Pins
Oscilloscope	PC0, PC5
Counter	PA0, PA1, PB14
Voltmeter	PC0, PC5
Signal Generator	PA4
Mod. PWM Generator	PA9, PB4
Pattern Generator	PC2, PC3, PC4, PC5, PC6, PC7, PC8, PC9
Sync PWM Generator	PC6, PC7, PC8, PC9
Voltage Source	PA4

Compatibility Matrix

Green = compatible | Red = conflict | Grey = self

	Scope	Counter	Voltm.	Sig.Gen	PWM Gen	Pattern	SyncPWM	Vout
Scope	-		X			X		
Counter		-						
Voltm.	X		-			X		
Sig.Gen				-	X	X		X
PWM Gen				X	-	X	X	
Pattern	X		X	X	X	-	X	
SyncPWM					X	X	-	
Vout				X				-

Nucleo-C562RE - Module Datasheet

Module Characteristics

Oscilloscope	
Channels	2
Max Sampling (12-bit)	2.25 MSps
Max Sampling (8-bit)	2.5 MSps
Interleaved (12-bit)	4.5 MSps
Interleaved (8-bit)	5 MSps
Interleaved Ch.	1
Buffer Size	64k samples
Resolution	12 / 8 bit

Counter	
HF Range Max	300 MHz
LF Range Max	1 MHz
Ref. Input Max	36 MHz
Counter Clock	144 MHz
Gate Clock	144 MHz

Voltmeter	
Channels	2
Resolution	12 bit
Buffer Size	64k samples

Signal Generator	
Channels	1
Max Speed	2 MSps
Resolution	12 bit
Buffer Size	20k samples
Timer Clock	144 MHz

Mod. PWM Generator	
Channels	2
Max Frequency	9.6 MHz
Timer Clock	144 MHz

Pattern Generator	
Channels	8
Data Shift	2

Sync PWM Generator	
Channels	4
Max Frequency	72 MHz
Ch. Independence	Paired

Voltage Source	
Channels	1
Resolution	12 bit